


# 9619-9819

**Max. 40,8 W**

## AC/DC SWITCH MODE PLUG-IN

9819 - medisinsk godkjent / medical approved  
(EN 60601) 12V / 24V version

- Faste utgangsspenninger
- Spesielt konstruert for IT-utstyr
- Utskiftbare DC plugger
- Tilgjengelig i 120 V versjon
- Fixed output voltages
- Specially designed for IT-equipment
- Exchangeable DC plugs
- Available in 120 V version


**9819**

<b>Tekniske data - 13,2 V versjon 9619</b>		<b>Technical specifications - 13,2 V version 9619</b>	
Inngangsspenning:		Input voltage:	190-264 VAC / 240-360 VDC 120V: 90+130VAC/127-180 VDC
Utgangsspenning:		Output voltage:	13,2 ± 0,1 VDC
• Innvendig justerbar:		• Internally adjustable:	10,0 - 15,0 V
Maks. utgangseffekt:		Max. output power:	36 W
Maks. laststrøm:		Max. load current:	2,4 A
Lastregulering:		Load regulation:	< 20 mV
Linjeregulering:		Line regulation:	< 20 mV
Svitsjefrekvens:		Switch frequency:	40 kHz
Temperaturområde:		Temperature range:	-10°C - +40°C
Rippel:		Ripple:	< 30 mV p-p 40 kHz/100 Hz
Strømbegrensning:		Current limiting:	Min. 2,6 A, max. 3,1 A
Overspenningsbeskyttelse:		Overvoltage protection:	Zener
Isolasjonsklasse:		Insulation class:	II
Elektrisk sikkerhetsstandard:		Electrical safety standard:	EN 60065, EN 60950
EMC standarder		EMC standards	
• Emisjon:		• Emission:	EN 61000-6-3
• Immunitet:		• Immunity:	EN 61000-6-1
Utgangsterminaler		Output terminals	
• Sek. ledning med/uten plugg:		• Cord with/without plug:	Tilbehør / Accessories
Mål uten plugg (LxBxH):		Dimensions without plug (LxWxH):	100 x 63 x 47 mm

Visse tekniske data kan variere for de forskjellige modeller og spenningsversjoner.  
Some technical specifications may differ for other models and voltage versions.

### Spenningsversjoner 9619 - Voltage versions 9619

Inngang (VAC) Input (VAC)	Utgang (VDC) Output (VDC)		Maks. strøm (A) Max. current (A)	Maks. utgangseffekt (W) Max. output power (W)
	Nom. Nom.	Innvendig justerbar Internally adjustable		
230	7,5	4,5 - 7,8	3,0	23,4
230	9	7,5 - 12,0	2,8	33,6
120* / 230	13,2	10,0 - 15,0	2,4	36
230	18,2	15,0 - 24,0	1,7	40,8
230	24,4	24,0 - 30,0	1,3	39

- \* UL godkjent (UL 1950)
- \* UL approved (UL 1950)

23052006

www.mascot.no  
sales@mascot.no  
Phone:  
Fax:

**Main Office**  
PO Box 177  
N-1601 FREDRIKSTAD  
NORWAY  
+47 69 36 43 00  
+47 69 36 43 01

**Mascot UK**  
Box 2090, Salisbury  
Wiltshire SP2 2BH  
UK  
+44 1722 504 853  
+44 845 299 1210

**Mascot DE-AT-CH-BENELUX**  
Hirschbergstr. 28/7  
D-74838 LIMBACH  
GERMANY  
+49 6287 95140  
+49 6287 95141

Tettninger Str. 52  
D-88239 WANGEN  
GERMANY  
+49 7528 95 16 77  
+49 7528 95 16 78

**Mascot France**  
38 rue Leo Lagrange  
94270 Le Kremlin Bicêtre  
FRANCE  
+33 1 46 58 71 85  
+33 1 46 58 71 85